



	Front Boss Dia.	Rear Boss Dia.	Boss Spacing C-to-C	Coupler Width	Lug Width	Lug Thickness
	A	B	C	D	E	F
Series 130	4.500"	4.500"	16.250"	13.3125"	13.5625"	1.000"
Series 150	5.375"	5.375"	15.500"	15.500"	15.625"	1.250"
Series 160	5.375"	5.375"	17.0625"	15.500"	15.625"	1.250"
Series 200	5.4375"	5.4375"	18.125"	16.500"	16.750"	1.500"
Series 250	6.500"	6.500"	18.250"	20.625"	20.875"	1.500"
Series 300	7.125"	7.125"	21.625"	21.0625"	21.375"	1.750"
Series 400	7.500"	7.500"	22.000"	23.375"	23.750"	2.000"
Series 550	9.000"	9.000"	24.500"	25.750"	26.250"	2.500"
Series 650	9.000"	9.000"	26.500"	26.500"	26.875"	2.500"

**CL = Center Line of Hangers**  
**DA = Lower Pin Diameter**  
**DB = Upper Pin Diameter**  
**R = Center of Lower Pin Hole to Center of Upper Pin Hole**  
**T = Hanger Thickness**

**JPHEQUIP.com**  
**SELLING MADE SIMPLE**  
**888-601-3350**

Make	Size	CL	Da	Db	R	T	Notes
ACS	1000	V Channel w/ Horz pins					
ACS	2000	V Channel w/ Vertical pins					
Balderson		Print and Special Quote Required					
CAT	IT12-IT28	22.37	2.01	2.49	19.93	1.50	
CAT	IT38	36.25	2.06	3.10	23.30	1.50	
Hyundai	730/740 TM	22.29	1.98	2.38	19.78	1.50	
Hyundai	757 TM	28.74	1.98	2.38	18.72	1.50	
John Deere	Hi Vis	39.38	1.99	2.42	24.47	1.50	Same as Volvo - Iso
John Deere	JRB						See Below
JRB	E	38.20	1.81	2.62	20.33	1.00	
JRB	580	29.80	1.56	2.03	17.32	1.50	
JRB	84	24.38	1.56	2.03	13.24	1.50	
JRB	416	30.62	2.06	3.03	16.75	1.50	
JRB	418	32.75	2.06	3.03	21.16	1.50	
JRB	420	29.00	2.06	4.03	22.11	2.00	
JRB	422	30.88	2.06	4.53	27.52	2.50	
Komatsu	WA65/75/85	35.12	1.59	1.59	12.3	1.25	
Volvo - ISO	L50-L120	39.27	2.01	2.42	24.47	1.50	
Volvo - ISO	L150-L220	39.27	2.01	2.42	24.47	1.73	

